

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

# Teflon Wire & Tubing

鐵氟龍凱那線  
 (POLYVINYLIDENE FLUORIDE) PVDF WIRE  
 **UL AWM Style # 1422,1423**

## SPECIFICATION

- Conductor :  
Silver Plated Copper
- Insulation :  
PVDF  
Thinner Wall
- Excellent tough and elongation
- Temperature Rating :  
105°C
- Voltage Rating :  
150 V,300V
- Colors :  
White,Red,Yellow,Green  
Blue,Black,Gray,Brown
- Application :  
Wire Wrapping,Testing Fixtures,  
Communication Cable Jacketing.



Communication cable jacketing  
200 pair-type 24AWG



## 說明

- 導體：鍍銀線
- 絕緣：PVDF 鐵氟龍  
絕緣壁薄，不佔空間
- 韌性高，不易破裂，延展性高，不易拉斷
- 耐熱溫度：150°C
- 耐高電壓：150V, 300V
- 顏色：白、紅、橘、黃、綠  
藍、黑、灰、棕
- 用途：測試治具，通訊絕緣用途

ULSTYLE NUMBER	CONDUCTOR		INSULATION THICKNESS	OVERALL DIAMETER
	AWG	DIAMETER	mm	mm ± 0.05
1423	34	0.16	0.08	0.32
1423	32	0.20	0.08	0.36
1423	30	0.25	0.125	0.50
1422	28	0.32	0.14	0.60
1422	26	0.40	0.15	0.70
1423	24	0.50	0.13	0.76